

Scientific Drilling's Standard FLS (Flow Logging System) is a high-quality and cost-effective flow profile defining solution.

This compact and modular system offers the following sensors for both memory and real-time data acquisition:

- + Casing collar locator (CCL)
- + Gamma ray
- + Pressure
- + Temperature
- + Spinner flowmeter
- + Fluid capacitance
- + Tuning fork density

For more information on Scientific Drilling's range of cased hole services, contact your Scientific Drilling sales representative or visit:

<http://scientificdrilling.com/cased-hole-services>

GENERAL SPECIFICATIONS

MAXIMUM TEMPERATURE**	325°F (163°C)
MAXIMUM PRESSURE	16,000 psi (110,316 kPa)
MEMORY	Non-volatile, 48 MB
TEMPERATURE SENSOR ACCURACY/RESOLUTION	High-accuracy platinum resistance ±1.8°F (1°C) / 0.02°F (0.01°C)
PRESSURE SENSOR ACCURACY/RESOLUTION	High Accuracy Quartz ±3.0 psi / 0.01 psi
FULLBORE SPINNER RESOLUTION, TYPE,	Minimum 0.1 rps with direction 4-Arm / 6-Arm
CONTINUOUS SPINNER RESOLUTION & OD RANGE	Minimum 0.1 rps with direction 1.5 - 3.5 in
GAMMA RAY CRYSTAL DETECTOR	Sodium iodide (NaI) scintillation
CASING COLLAR LOCATOR TYPE & MEASUREMENT FREQUENCY	Magnetic Flux 50 samples per second
TUNING FORK DENSITY ACCURACY / RESOLUTION & RANGE	0.003 g/cc / ±0.001 g/cc 0.0 g/cc – 1.2 g/cc
CAPACITANCE RANGE	0 - 100% (Dependent on water hold-up)
CENTRALIZERS	Over-body or In-line
HOUSING DIAMETER	1.38 in (350 mm)

*Specifications are subject to change without notice **Max. temperature rating dependent on run duration



APPLICATIONS

- + Multiphase flow profiling
- + Leak Detection
- + Water & gas injector flow profiling
- + High flow rate gas wells
- + Memory and real-time data acquisition

BENEFITS

- + Slickline conveyance simplifies pressure control for safer operations
- + Batteries can be adapted for extended runs (~ 10 days)
- + Tuning fork density provides superior quality density data in high gas flow conditions